

Cursive Arabic Handwriting Recognition System Without Explicit Segmentation Based on Hidden Markov Models

Mouhcine Rabi, Mustapha Amrouch, Zouhair Mahani

► **To cite this version:**

Mouhcine Rabi, Mustapha Amrouch, Zouhair Mahani. Cursive Arabic Handwriting Recognition System Without Explicit Segmentation Based on Hidden Markov Models. *Journal of Data Mining and Digital Humanities*, Episciences.org, 2018, Special Issue on Scientific and Technological Strategic Intelligence (2016). hal-01458216

HAL Id: hal-01458216

<https://hal.archives-ouvertes.fr/hal-01458216>

Submitted on 9 Feb 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Cursive Arabic Handwriting Recognition System Without Explicit Segmentation Based on Hidden Markov Models

Mouhcine RABI^{*}, Mustapha AMROUCH¹, Zouhair MAHANI²

1 Laboratory IRF-SIC, faculty of sciences Ibn Zohr University, Agadir, Morocco
2 High School of Technology, Ibn Zohr University, Agadir, Morocco

*mouhcineh@gmail.com
m.amrouch@uiz.ac.ma
zouhir.mahani@gmail.com

Abstract

In this paper we present a system for offline recognition cursive Arabic handwritten text which is analytical without explicit segmentation based on Hidden Markov Models (HMMs). Extraction features preceded by baseline estimation are statistical and geometric to integrate both the peculiarities of the text and the pixel distribution characteristics in the word image. These features are modelled using hidden Markov models. The HMM-based classifier contains a training module and a recognition module. The training module estimates the parameters of each of the character HMMs uses the Baum-Welch algorithm. In the recognition phase, feature vectors extracted from an image are passed to a network of word lexicon entries formed of character models. The character sequence providing the maximum likelihood identifies the recognized entry. If required, the recognition can generate N best output hypotheses rather than just the single best one. To determine the best output hypotheses, the Viterbi algorithm is used. The experiments on images of the benchmark IFN/ENIT database show that the proposed system improves recognition.

Keywords

Recognition; handwriting; Arabic text; HMMs.

I INTRODUCTION

The recognition of cursive Arabic handwriting is an active area of pattern recognition research. The variability of words, letter shapes are context sensitive, inter and intra word spaces, the cursive nature of Arabic handwriting, the skew and slant of characters and words makes the construction of offline recognition system a challenging task.

Researches have tried various approaches for text recognition employing various techniques for pre-processing, feature extraction and classification [A. Lawgali 2015].

The subject of this article concerns the recognition of cursive Arabic handwriting [M.T Parvez 2013] [AL-Shatnawi 2011]. Several systems are available based on two approaches; a global approach that considers the word as non-divisible base entity avoiding the segmentation process and its problems. This approach is reliable and applicable for vocabularies of limited size. Against, the analytical approach is based on the decomposition of the word sequence into characters or graphemes proceeding by a segmentation phase. The latter can be explicitly based on a priori division of the image into subunits (letters or grapheme) or implicitly based on a recognition engine to validate and rank the segmentation hypothesis. The approach used in our system is analytical based on implicit segmentation; segmentation and recognition are carried out jointly.

The first step of a handwriting recognition system after preprocessing is the extraction features. The objective of this phase is the selection of primitives relevant for the next steps of classification and recognition. The performance of a recognition handwritten system largely depends on the quality and the relevance of the extracted features. In our system after the baselines estimation, the extracted features are statistics acting on the densities of pixels and structural extracted from the representation of the character shapes.

Hidden Markov models (HMMs) are used for classification [S.Azeem 2013] [AlKhateeb 2011][A. Maqqor 2014]. There are many reasons for success of HMMs in text recognition including avoidance of the need to explicitly segmentation. In addition, HMMs have sound mathematical and theoretical foundations. Each word is described by a model built by concatenating the models of the component character. The system performs training and recognition of words and characters.




Figure 1 presents the synopsis of the proposed system.

The remainder of this paper is organized as follow. Section 2 presents a detailed description of the features extraction preceded by baselines estimation. Section 3 is focused on classification step. The performance of the recognition system has been experimented on the benchmark database IFN/ENIT and the obtained experimental results are shown and analysed in section 4. The paper finally concludes with some conclusions and perspectives.

II EXTRACTION FEATURES

1.1 Baseline Estimation

The goal is to find, for a given word, the positions of the two following parallel lines (Figure 2):

- Lower baseline (LB),
- Upper baseline (UB).

These baselines divide the image into lower, upper and middle zone.




Figure 2. Lower and upper baselines estimation

Several techniques exist for estimating these two lines, horizontal projection histogram, the Hough transform, the minima of the bottom contours [Farooq et al, 2005], the neighborhood approach and components, PCA (Principal Component Analysis) [B. Su, X. Ding 2013] [O. Morillot 2013].

The approach used is based on the horizontal projection curve that is computed with respect to the horizontal pixel density, knowing that the skew and slant correction of words are made in preprocessing step to harmonize the course of the sliding windows in the extraction features. LB corresponds to the maximum of the projection profile curve, then, the algorithm scans the image from top to bottom to find the upper baseline, which corresponds to the first line with a projection value higher or equal to the average row density. Thus, the handwritten variability of word in both zones, upper and lower are considered.

1.2 Extraction Features

The features extraction method used in our system is inspired by work of El-Hajj [El-Hajj 2009] with some modifications; the used technique has shown excellent results in several researches [A-L. B-Bernard 2012] [T. Bluche 2015]. The features extraction stage consists of extracting a sequence of characteristics vector by dividing the word image into vertical frames. The sliding windows are shifted in the direction of writing (right to left). The width of each window is a parameter to set, the height of a window varies according to the dimension of the word image.

In each window we extract a set of 28 features represent the distribution features based on foreground pixels densities and concavity features. Each window is divided into a fixed number of cells. Some of these features are extracted from specific areas of the image delimited by the word baselines.

In our experimentation the parameters are set to $n = 20$ cells and the width = 8 pixels. This leads to a total of $N_f = 28$ to calculate in each frame.

Let:

- $n(i)$: the number of foreground pixels in cell i
- $r(j)$: the number of foreground pixels in the j th row of a frame.
- $b(i)$: the density level of cell i : $b(i) = 0$ if $n(i) = 0$ else $b(i) = 1$.

The extracted features are the following:

$f1$: density of foreground (black) pixels.

$$f1 = \frac{1}{H \times w} \sum_{i=1}^{n_c} n(i)$$

$f2$: number of transitions black/white between two consecutive cells.

$$f2 = \sum_{i=2}^{n_c} |b(i) - b(i-1)|$$

f3: difference's position of gravity centers of foreground pixels in two consecutive frame(current and previous)

$$f3 = g(t) - g(t-1)$$

f4: normalized vertical position of the center of gravity of the foreground pixels in the whole frame with respect to the lower baseline.

$$f4 = \frac{g-L}{H}$$

f5, f6: represent the density of foreground pixels over and under the lower baselines.

$$f5 = \frac{\sum_{j=L+1}^H r(j)}{H.w} ; \quad f6 = \frac{\sum_{j=1}^{L-1} r(j)}{H.w}$$

f7: number of transitions black/white between two consecutive cells of different density levels above the lower baseline.

$$f7 = \sum_{i=k}^{n_c} |b(i) - b(i-1)|$$

f8: zone to which the gravity center of blk pixels belongs (lower zone f8=3, middle zone f8=2, upper zone f8=1)

f9,..., f14: the concavity features are defined as:

$$f9 = \frac{C_{left-up}}{H} ;$$

$C_{left-up}$: the number of background pixels that have neighbor black pixels in the two directions (left and up)

The same applies to f9, ..., f14 in six directions left-up, up-right, right-down, down-left, vertical and horizontal.

f15, ..., f20 : the baseline dependent features related to the core zone are defined as :

$$f15 = \frac{CM_{left-up}}{d} ;$$

$CM_{left-up}$: the number of background pixels in the configuration left-up

The same applies to f16, ..., f20 in six directions left-up, up-right, right-down, down-left, vertical and horizontal.

f21,..., f28 : represent the density of foreground pixels in each vertical column in a frame.

In each frame 28 features vector are extracted, these features are statistical and geometric to integrate both the peculiarities of the text and the pixel distribution characteristics in the word image, which capture the type of strokes (curved, oriented, vertical, and horizontal).

IIIMODELING

2.1Hidden Markov Models

A Hidden Markov Model (HMM) is a doubly stochastic process with an under-lined stochastic process (Markov chain) that is not observable (it is hidden), but can only be observed

through another set of stochastic processes that produce the sequence of observed symbols [Rabiner, 1989]. In order to define an HMM completely, following elements are needed, $\lambda = (N, M, A, B, \Pi)$:

- N: The number of states of the model,
- M: The number of observation symbols in the alphabet. If the observations are continuous then M is infinite,
- A : A set of state transition probabilities,
- B: A probability distribution in each of the states,
- Π : The initial state distribution.

The use of HMM aims to resolve three problems:

❖ The Evaluation

Given an HMM λ and a sequence of observations $O=o_1, o_2, \dots, o_T$, what is the probability that the observations are generated by the model, $P\{O|\lambda\}$

❖ The Decoding

Given a model λ and a sequence of observations $O=o_1, o_2, \dots, o_T$, what is the most likely state sequence in the model that produced the observations?

❖ The Training

Given a model λ and a sequence of observations $O=o_1, o_2, \dots, o_T$, how should we adjust the model parameters $\{\Pi, A, B\}$ in order to maximize $P\{O|\lambda\}$

2.2 Character and word models

The used approach is analytical and based on character modeling by HMM. Each character model has a right-left topology and parameters: number of hidden states, state transition probabilities and observation probabilities.

There is no specific theory to set these parameters, so the solution is empirical. Many considerations can be taken into account in setting these parameters and in particular the technique used in the generation of sequences of observations. In our system we used a model with four states for each character with three transitions for each state (Figure 3).




Figure 3. Character HMM topology

Word model is built by concatenating the appropriate character models (figure 4).




Figure 4. HMM model for Arabic word : مليشات

IV. EXPERIMENTATIONS AND RESULTS

In order to investigate the potential of our system for offline cursive handwriting recognition, the benchmark database IFN/ENIT is used [Peschwitz 2003], that contains a total of 26459 handwritten words of 946 Tunisian town/villages names written by different writers. We used

the toolbox HTK (Hidden Markov Model Toolkit[S.Young 2006]) to model the characters and words.

The table below shows the experimental results of our system compared to other recognition systems using the same benchmarking database IFN/ENIT, divided into four sets a, b, c for training and d for testing :

Table 1: Recognition results of various systems

<i>System</i>	<i>Models</i>	<i>Recognition rate %</i>
[Kessentini et al 2010]	Multi Stream HMM	79.80
[Alkhateeb et al. 2011]	HMM and dynamic Bayesian network	86.73
[Parvez et al. 2013]	FATF with set medians	79.58
[A.Maqqor 2014]	Multiple Classifiers	76.54
Proposed System	HMM	87.93

Table 1 shows the results of recognition rates for various offline systems recognition of cursive Arabic handwritten text using various models and the same database to compare rates and infer the effectiveness of the proposed method.

[Alkhateeb et al. 2011] are presented a comparative study of approaches for recognizing handwritten Arabic words using Hidden Markov Models (HMM) and Dynamic Bayesian Network (DBN) classifiers, and The recognition rate achieved was 86,73%. [Kessentini et al 2010] [Parvez et al. 2013][A.Maqqor 2014] are presented systems using respectively a multi-stream Hidden Markov Models, Fuzzy Attributed Turning Function (FATF) with set-medians; the recognition rate for the results of the systems mentioned does not exceed 80%. Whereas the proposed system outperforms the results and achieves 87.93%.

Finally, the performance of handwritten Arabic recognition system is significantly improved using our system based on HMMs. It remains to boost the rate using annexes improvements (Post-Processing: language models)

V. CONCLUSION & PERSPECTIVES

In this paper, we present a recognition system of Arabic cursive handwriting based on hidden Markov models. The extracted features are based on the densities of foreground pixels, concavity and derivative features using sliding window, some of these features depends on baseline estimation. The modelling proposed has improved recognition, and shown encouraging results to be perfect later. Many points are yet to be achieved, firstly modeling a character allows deformations related to its context (next and previous character). To account possible deformations, contextual modeling of characters is opted. The word is no longer seen as a succession of independent characters, but as a sequence of characters in context. Word models are the concatenation of context-dependent characters models: the trigraphe, this modelling will allow building more accurate and more efficient models. Taking into account the characters environment allows more precise and more effective models to be built. However, this implies a multiplication of HMM parameters to be learned, it would be the focus of our next work. Then language models will be incorporated to refine and improve the results and lead to a more efficient system.

References

- A.Lawgali : “A Survey on Arabic Character Recognition” International Journal of Signal Processing, Image Processing and Pattern Recognition. Vol. 8, No. 2 (2015), pp. 401-426.
- ThéodoreBluche, Hermann Ney, Christopher Kermorvant (2015) The LIMSI Handwriting Recognition System for the HTRtS 2014 Contest. In International Conference of Document Analysis and Recognition (ICDAR).
- Ahmad, I., Fink, G.A., Mahmoud, S.A.: Improvements in sub-character HMM model based Arabic text recognition. In: ICFHR (2014)
- M.T Parvez and S.A Mahmoud “ Offline Arabic handwritten text recognition : A survey “ ACM ComputSurvvol 45 no 2 pp 23-35 May 2013
- S. Azeem and H. Ahmed, “Effective technique for the recognition of offline Arabic handwritten words using hidden Markov models,” Int. J. Doc. Anal.Recognit., vol. 16, no. 4, pp.399– 412, 2013.
- B. Su, X. Ding, L. Peng, and C. Liu, “A Novel Baseline independent Feature Set for Arabic Handwriting Recognition,” in Document Analysis and Recognition (ICDAR), 2013 12th International Conference on, 2013, pp. 1250–1254.
- C. Choisy et A. Belaid « Apprentissage croisé en reconnaissance analytique de l’écriture manuscrite » colloque international francophone sur l’écrit et le Document 2000.
- S. Young, al., the HTK Book V3.4 Cambridge University Press, Cambridge UK, 2006
- L.R. Rabiner : “A tutorial on Hidden Markov Models and selected applications in speech recognition”. Proceedings of the IEEE, 77(2) :257- 286, 1989.
- O. Morillot “New baseline correction algorithm for text-line recognition with bidirectional recurrent neural networks” Journal of Electronic Imaging 22(2), 023028 (Apr–Jun 2013)
- A. Maqqor, A. Halli, K. Satori, and H. Tairi, Off-line recognition Handwriting combination of multiple classifiers, In 3rd International IEEE Colloquium on Information Science and Technology, IEEE CIST’14, October 2014.
- M. T. Parvez, A. M. Sabri, Arabic handwriting recognition using structural and syntactic pattern attributes, in Pattern Recognition 46 (2013), pp. 141-154.
- Anne-laureBianne-bernard, Fares Menasri, Laurence Likforman-sulem, ChaficMokbel, Christopher Kermorvant (2012) Variable length and context-dependent HMM letter form models for Arabic handwritten word recognition. In Document Recognition and Retrieval Conference (DRR)
- AL-Shatnawi, M. Atallah, AL-Salaimah, Safwan, AL-Zawaideh, Farah Hanna, Omar, Khairuddin, Offline arabic text recognition an overview, World Comput. Sci. Inform. Technol. J. 1 (5), 184–192, 2011.
- J. AlKhateeb, H., Ren, Jinchang, Jiang, Jianmin, Al-Muhtaseb, Husni, Offline handwritten arabic cursive text recognition using hidden markov models and re-ranking, Pattern Recognition Lett. 32 (8), 1081–1088, 2011.
- J. H. Alkhateeb, O. Pauplin, J. Ren, J. Jiang, Performance of hidden Markov model and dynamic Bayesian network classifiers on handwritten Arabic word recognition, In Knowledge-Based Systems 24 (2011), pp.680-688.
- Y. Kessentini, T. Paquet, A. Ben Hamadou, Off-line handwritten word recognition using multistream hidden Markov models, in: Pattern Recognition Letters 31 (2010), pp. 60-70
- L.R. Rabiner : “A tutorial on Hidden Markov Models and selected applications in speech recognition”. Proceedings of the IEEE, 77(2) :257- 286, 1989.
- Pechwitz M. and Maergner V., "Baseline estimation for Arabic handwritten words", in Proc. of the 8th IWFHR 2002, pp 479-484, Canada, August (2002).
- Farooq F., Govindaraju V., Perrone M., "Pre-processing methods for handwritten Arabic Documents", ICDAR’05.pp: 267-271, Seoul (2005).
- EL-Hajj R R. Likforman-Sulem L. Mokbel C., “ Combining Slanted-Frames Classifiers for Improved HMM-Based Arabic Handwriting Recognition”, IEEE Transactions on Pattern Analysis and Machine Intelligence, 2009.